

CDR

CDR

CDR

CDR

CDR

CDR

CDR

CDR

CDR

CDR

CDR

CDR

液晶触摸屏，配置RS232、RS485等接口，选配SNMP

卡，可实现UPS智能化监控。

技术参数

规格型号	10KL	15KL	20KL	30KL	40KL	60KL	80KL	100KL	120KL	160KL	200KL	250KL	300KL
额定功率 (kW)	8	12	16	24	32	48	64	80	96	128	160	200	240
市电输入													
输入电压范围	380VAC±25%												
输入频率范围	50Hz/60Hz±5%(可选±10%)												
输入功率因数	≥0.95												
输出电源													
输出电压及精度	380VAC±1%												
输出频率及精度	市电同步, 50/60Hz±1Hz; 逆变状态, 50/60Hz±0.1Hz												
电压相位偏差	120°±1°												
并机负载电流不平衡度	≤5%												
电压不平衡度	平衡负载 < 1%; 50%不平衡负载 < 3%; 100%不平衡负载 < 5%												
波形失真度	纯正弦波, 阻性负载时≤2%; 非线性负载时≤3%												
过载能力	过载 125%可持续 10 分钟; 过载 150%可持续 60 秒												
电流峰值比	5:1												
电池													
电池类型	磷酸铁锂电池												
电池容量	100kWh/200kWh/300kWh/400kWh/500kWh/600kWh/800kWh/1000kWh												
电池电压	51.2V/51.8V/52.4V/53.0V/53.6V/54.2V/54.8V/55.4V/56.0V/56.6V/57.2V/57.8V/58.4V/59.0V/59.6V/60.2V/60.8V/61.4V/62.0V/62.6V/63.2V/63.8V/64.4V/65.0V/65.6V/66.2V/66.8V/67.4V/68.0V/68.6V/69.2V/69.8V/70.4V/71.0V/71.6V/72.2V/72.8V/73.4V/74.0V/74.6V/75.2V/75.8V/76.4V/77.0V/77.6V/78.2V/78.8V/79.4V/80.0V/80.6V/81.2V/81.8V/82.4V/83.0V/83.6V/84.2V/84.8V/85.4V/86.0V/86.6V/87.2V/87.8V/88.4V/89.0V/89.6V/90.2V/90.8V/91.4V/92.0V/92.6V/93.2V/93.8V/94.4V/95.0V/95.6V/96.2V/96.8V/97.4V/98.0V/98.6V/99.2V/99.8V/100.4V/101.0V/101.6V/102.2V/102.8V/103.4V/104.0V/104.6V/105.2V/105.8V/106.4V/107.0V/107.6V/108.2V/108.8V/109.4V/110.0V/110.6V/111.2V/111.8V/112.4V/113.0V/113.6V/114.2V/114.8V/115.4V/116.0V/116.6V/117.2V/117.8V/118.4V/119.0V/119.6V/120.2V/120.8V/121.4V/122.0V/122.6V/123.2V/123.8V/124.4V/125.0V/125.6V/126.2V/126.8V/127.4V/128.0V/128.6V/129.2V/129.8V/130.4V/131.0V/131.6V/132.2V/132.8V/133.4V/134.0V/134.6V/135.2V/135.8V/136.4V/137.0V/137.6V/138.2V/138.8V/139.4V/140.0V/140.6V/141.2V/141.8V/142.4V/143.0V/143.6V/144.2V/144.8V/145.4V/146.0V/146.6V/147.2V/147.8V/148.4V/149.0V/149.6V/150.2V/150.8V/151.4V/152.0V/152.6V/153.2V/153.8V/154.4V/155.0V/155.6V/156.2V/156.8V/157.4V/158.0V/158.6V/159.2V/159.8V/160.4V/161.0V/161.6V/162.2V/162.8V/163.4V/164.0V/164.6V/165.2V/165.8V/166.4V/167.0V/167.6V/168.2V/168.8V/169.4V/170.0V/170.6V/171.2V/171.8V/172.4V/173.0V/173.6V/174.2V/174.8V/175.4V/176.0V/176.6V/177.2V/177.8V/178.4V/179.0V/179.6V/180.2V/180.8V/181.4V/182.0V/182.6V/183.2V/183.8V/184.4V/185.0V/185.6V/186.2V/186.8V/187.4V/188.0V/188.6V/189.2V/189.8V/190.4V/191.0V/191.6V/192.2V/192.8V/193.4V/194.0V/194.6V/195.2V/195.8V/196.4V/197.0V/197.6V/198.2V/198.8V/199.4V/200.0V/200.6V/201.2V/201.8V/202.4V/203.0V/203.6V/204.2V/204.8V/205.4V/206.0V/206.6V/207.2V/207.8V/208.4V/209.0V/209.6V/210.2V/210.8V/211.4V/212.0V/212.6V/213.2V/213.8V/214.4V/215.0V/215.6V/216.2V/216.8V/217.4V/218.0V/218.6V/219.2V/219.8V/220.4V/221.0V/221.6V/222.2V/222.8V/223.4V/224.0V/224.6V/225.2V/225.8V/226.4V/227.0V/227.6V/228.2V/228.8V/229.4V/230.0V/230.6V/231.2V/231.8V/232.4V/233.0V/233.6V/234.2V/234.8V/235.4V/236.0V/236.6V/237.2V/237.8V/238.4V/239.0V/239.6V/240.2V/240.8V/241.4V/242.0V/242.6V/243.2V/243.8V/244.4V/245.0V/245.6V/246.2V/246.8V/247.4V/248.0V/248.6V/249.2V/249.8V/250.4V/251.0V/251.6V/252.2V/252.8V/253.4V/254.0V/254.6V/255.2V/255.8V/256.4V/257.0V/257.6V/258.2V/258.8V/259.4V/260.0V/260.6V/261.2V/261.8V/262.4V/263.0V/263.6V/264.2V/264.8V/265.4V/266.0V/266.6V/267.2V/267.8V/268.4V/269.0V/269.6V/270.2V/270.8V/271.4V/272.0V/272.6V/273.2V/273.8V/274.4V/275.0V/275.6V/276.2V/276.8V/277.4V/278.0V/278.6V/279.2V/279.8V/280.4V/281.0V/281.6V/282.2V/282.8V/283.4V/284.0V/284.6V/285.2V/285.8V/286.4V/287.0V/287.6V/288.2V/288.8V/289.4V/290.0V/290.6V/291.2V/291.8V/292.4V/293.0V/293.6V/294.2V/294.8V/295.4V/296.0V/296.6V/297.2V/297.8V/298.4V/299.0V/299.6V/300.2V/300.8V/301.4V/302.0V/302.6V/303.2V/303.8V/304.4V/305.0V/305.6V/306.2V/306.8V/307.4V/308.0V/308.6V/309.2V/309.8V/310.4V/311.0V/311.6V/312.2V/312.8V/313.4V/314.0V/314.6V/315.2V/315.8V/316.4V/317.0V/317.6V/318.2V/318.8V/319.4V/320.0V/320.6V/321.2V/321.8V/322.4V/323.0V/323.6V/324.2V/324.8V/325.4V/326.0V/326.6V/327.2V/327.8V/328.4V/329.0V/329.6V/330.2V/330.8V/331.4V/332.0V/332.6V/333.2V/333.8V/334.4V/335.0V/335.6V/336.2V/336.8V/337.4V/338.0V/338.6V/339.2V/339.8V/340.4V/341.0V/341.6V/342.2V/342.8V/												

[illegible]


THERMAL ANALYSIS DATA						THERMAL ANALYSIS DATA			
5	500	400	300	200	100	000	1100	1200	1300
10	400	300	200	100	000	700	800	900	1000

時間	場所	出席者	欠席者	出席率
10月10日	10月10日	10月10日	10月10日	10月10日

三、問題：
1. 如何處理？

① 2019 年 12 月 31 日，该设备已计提折旧 100 万元。

Copyright © 2004 John Wiley & Sons, Ltd.



技术参数

规格型号	10KL	15KL	20KL	30KL	40KL	60KL	80KL	100KL	120KL	160KL	200KL
额定功率（kW）	8	12	16	24	32	48	64	80	96	128	160
市电输入											
输入电压范围	380VAC±25%										

1. 额定功率

2. 额定电压

3. 额定电流

4. 额定功率因数

5. 额定效率

6. 额定转速

7. 额定转矩

8. 额定功率

9. 额定电压

10. 额定电流

11. 额定功率因数

12. 额定效率

13. 额定转速

14. 额定转矩

15. 额定功率

16. 额定电压

17. 额定电流

18. 额定功率因数

19. 额定效率

20. 额定转速

21. 额定转矩

22. 额定功率

23. 额定电压

24. 额定电流

25. 额定功率因数

26. 额定效率

27. 额定转速

28. 额定转矩

29. 额定功率

30. 额定电压

31. 额定电流

32. 额定功率因数

33. 额定效率

34. 额定转速

35. 额定转矩

36. 额定功率

37. 额定电压

38. 额定电流

39. 额定功率因数

40. 额定效率

41. 额定转速

42. 额定转矩

43. 额定功率

44. 额定电压

45. 额定电流

46. 额定功率因数

47. 额定效率

48. 额定转速

49. 额定转矩

50. 额定功率

51. 额定电压

52. 额定电流

53. 额定功率因数

54. 额定效率

55. 额定转速

56. 额定转矩

57. 额定功率

58. 额定电压

59. 额定电流

60. 额定功率因数

61. 额定效率

62. 额定转速

63. 额定转矩

64. 额定功率

65. 额定电压

66. 额定电流

67. 额定功率因数

68. 额定效率

69. 额定转速

70. 额定转矩

71. 额定功率

72. 额定电压

73. 额定电流

74. 额定功率因数

75. 额定效率

76. 额定转速

77. 额定转矩

78. 额定功率

79. 额定电压

80. 额定电流

81. 额定功率因数

82. 额定效率

83. 额定转速

84. 额定转矩

85. 额定功率

86. 额定电压

87. 额定电流

88. 额定功率因数

89. 额定效率

90. 额定转速

91. 额定转矩

92. 额定功率

93. 额定电压

94. 额定电流

95. 额定功率因数

96. 额定效率

97. 额定转速

98. 额定转矩

99. 额定功率

100. 额定电压

101. 额定电流

102. 额定功率因数

103. 额定效率

104. 额定转速

105. 额定转矩

106. 额定功率

107. 额定电压

108. 额定电流

109. 额定功率因数

110. 额定效率

111. 额定转速

112. 额定转矩

113. 额定功率

114. 额定电压

115. 额定电流

116. 额定功率因数

117. 额定效率

118. 额定转速

119. 额定转矩

120. 额定功率

121. 额定电压

122. 额定电流

123. 额定功率因数

124. 额定效率

125. 额定转速

126. 额定转矩

127. 额定功率

128. 额定电压

129. 额定电流

130. 额定功率因数

131. 额定效率

132. 额定转速

133. 额定转矩

134. 额定功率

135. 额定电压

136. 额定电流

137. 额定功率因数

138. 额定效率

139. 额定转速

140. 额定转矩

141. 额定功率

142. 额定电压

143. 额定电流

144. 额定功率因数

145. 额定效率

146. 额定转速

147. 额定转矩

148. 额定功率

149. 额定电压

150. 额定电流

151. 额定功率因数

152. 额定效率

153. 额定转速

154. 额定转矩

155. 额定功率

156. 额定电压

157. 额定电流

158. 额定功率因数

159. 额定效率

160. 额定转速

161. 额定转矩

162. 额定功率

163. 额定电压

164. 额定电流

165. 额定功率因数

166. 额定效率

167. 额定转速

168. 额定转矩

169. 额定功率

170. 额定电压

171. 额定电流

172. 额定功率因数

173. 额定效率

174. 额定转速

175. 额定转矩

176. 额定功率

177. 额定电压

178. 额定电流

179. 额定功率因数

180. 额定效率

181. 额定转速

182. 额定转矩

183. 额定功率

184. 额定电压

185. 额定电流

186. 额定功率因数

187. 额定效率

188. 额定转速

189. 额定转矩

190. 额定功率

191. 额定电压

192. 额定电流

193. 额定功率因数

194. 额定效率

195. 额定转速

196. 额定转矩

197. 额定功率

198. 额定电压

199. 额定电流

200. 额定功率因数

201. 额定效率

202. 额定转速

203. 额定转矩

204. 额定功率

205. 额定电压

206. 额定电流

207. 额定功率因数

208. 额定效率

209. 额定转速

210. 额定转矩

211. 额定功率

212. 额定电压

213. 额定电流

214. 额定功率因数

215. 额定效率

216. 额定转速

217. 额定转矩

218. 额定功率

219. 额定电压

220. 额定电流

221. 额定功率因数

222. 额定效率

223. 额定转速

224. 额定转矩

225. 额定功率

226. 额定电压

227. 额定电流

228. 额定功率因数

229. 额定效率

230. 额定转速

231. 额定转矩

232. 额定功率

233. 额定电压

234. 额定电流

235. 额定功率因数

236. 额定效率

237. 额定转速

238. 额定转矩

239. 额定功率

240. 额定电压

241. 额定电流

242. 额定功率因数

243. 额定效率

244. 额定转速

245. 额定转矩

246. 额定功率

247. 额定电压

248. 额定电流

249. 额定功率因数

250. 额定效率

251. 额定转速

252. 额定转矩

253. 额定功率

254. 额定电压

255. 额定电流

256. 额定功率因数

257. 额定效率

258. 额定转速

259. 额定转矩

260. 额定功率

261. 额定电压

262. 额定电流

263. 额定功率因数

264. 额定效率

265. 额定转速

266. 额定转矩

267. 额定功率

268. 额定电压

269. 额定电流

270. 额定功率因数

271. 额定效率

272. 额定转速

273. 额定转矩

274. 额定功率

275. 额定电压

276. 额定电流

277. 额定功率因数

278. 额定效率

279. 额定转速

280. 额定转矩

281. 额定功率

282. 额定电压

283. 额定电流

284. 额定功率因数

285. 额定效率

技术参数

规格型号					市电输入		
额定功率 (kW)					输入电压范围		
300KL					输入频率范围		
400KL					输入功率因数		
500KL					输出电源		
600KL					输出电压及精度		
700KL					输出频率及精度		
800KL					电压相位偏差		
1000KL					总谐波畸变率		
380VAC±25%					输出不平衡度		
50/60Hz±1%; 50/60Hz±1.0%					输出效率		
≥0.99					过载能力		
380VAC±1%					电流峰值比		
电同步, 50/60Hz±1Hz; 逆变状态, 50/60Hz±0.1Hz					电池		
120°±1°					额定容量		
≤5%					配置方式		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					外置, 64节/12V		
过载 125%可持续 10 分钟; 过载 150%可持续 600秒					环境		
5:1					噪音		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					环境湿度		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					外形尺寸		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					宽×深×高 (mm)		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					净量(kg)		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					总重(kg)		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					3075		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					3530		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					4350		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					4830		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					5360		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					2230		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					2620		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					2240		
≤0.5% (满载); ≤0.3% (半载); ≤0.1% (空载)					2750		